



In-place MEMS Tilt Meter

MEMS
TILT & INCLINATION
SERIES**rst**
INSTRUMENTS**GEOSENSE**Official RST distributor in
Europe & MENAGeotechnical Centre
Rougham Industrial Estate
Rougham, Bury St Edmunds
Suffolk IP30 9ND
ENGLAND
Telephone: +44(0)1359 271167
Facsimile: +44(0)1359 271168
Geosense is a division of
Marton Geotechnical Services Ltd

info@mgsgeosense.co.uk

www.mgsgeosense.co.uk

ISO 9001:2000
REGISTERED QUALITY SYSTEMIn-place MEMS Tilt Meter shown
with Vertical Mounting Bracket.

RST's MEMS In-Place Tilt Meters are utilized to measure tilt in either one or two axial planes perpendicular to the surface of the base plate. The unit is intended to be permanently installed to provide long term observation with maximum resolution and sensitivity, and is conveniently designed for manual monitoring or remote data acquisition.

MEMS systems consist of a tiltmeter mounting plate, interconnecting cable, and data logger or readout instrument. The tiltmeter may either be uniaxial or biaxial and is available in both horizontal and vertical versions. The electronics are housed in a NEMA 4X (IP-65) enclosure for environmental protection, and is typically bolted or bonded to the structure. For maximum resistance against water ingress, the cable is typically hard wired to the enclosure; however connectors may be provided if required. The interconnecting cable is suitable for direct burial, and is available in an armoured version to suit demanding site conditions.

specifications

ITEM	DESCRIPTION
Range	±15° (other ranges upon request)
Resolution	±5 arc sec. (±0.025 mm/m) (10Hz BW) (or better, readout method dependent)
Non-linearity	±0.1% F.S.
Sensor	MEMS (Micro-Electro-Mechanical Systems) Inclinometer
Excitation	8 - 15V DC
Operating Temp.	-40 to 85°C (-40 to 185°F)
Dimensions	80 x 80 x 61mm (3.15 x 3.15 x 2.4 in.) Optional submersible unit's dimensions available upon request.

ordering info

UNIAXIAL	PART #
MEMS Uniaxial Tiltmeter - analog voltage	IC6550
MEMS Uniaxial Tiltmeter - 4-20mA	IC6552
MEMS Uniaxial Tiltmeter - digital output	IC6554
MEMS Uniaxial Tiltmeter - digital bus output	IC6556
MEMS Uniaxial Tiltmeter - frequency	IC6558
BIAXIAL	PART #
MEMS Biaxial Tiltmeter - analog voltage	IC6650
MEMS Biaxial Tiltmeter - 4-20mA	IC6652
MEMS Biaxial Tiltmeter - digital output	IC6654
MEMS Biaxial Tiltmeter - digital bus output	IC6656
MEMS Biaxial Tiltmeter - frequency	IC6658
MOUNTING	PART #
MEMS Tiltmeter Horizontal Mounting Plate	IC6700
MEMS Tiltmeter Vertical Mounting Bracket	IC6705
READOUTS & DATALOGGERS	PART #
Readout for MEMS Analog Voltage Tiltmeters	IC6800-V
flexDAQ Dataloggers	

applications

- Monitor tilt of retaining and building walls.
- Tilt of concrete dams.
- Structural load testing.
- Landslide monitoring.
- Building safety along adjacent excavations.
- Applications where the failure mode is expected to have a rotational component.
- Observation of benches and berms in open pit mines.
- Bridge pier monitoring.
- Ground subsidence.

features

- Uniaxial or biaxial sensors available.
- Horizontal or vertical applications.
- Analog, digital and frequency outputs available.
- Digital bus available.
- Data logger and/or manual readout compatible.
- High accuracy and repeatability.
- Easy to install.
- Cost effective.
- NEMA 4X (IP-65) weather-proof enclosure.

WORKS WITH

flexDAQ
DATALOGGERS
custom, turn-key datalogger
systems shipped "ready to run"RST Instruments Ltd. reserves the right
to change specifications without notice.